

Electrical insulation tape

Hellertape: HT2 and HT3, PVC (colour)

- Operating temperature -10°C to +80°C
- Cold and weather resistant
- Flame retardant
- Unaffected by moisture and most chemicals
- Good ageing characteristics
- No flapping or deterioration even under high temperatures

Technical Data

Description	HTS	HT3
Adhesion (N/cm)	1.8	1.6
Tensile strength (N/cm)	26	17
Elongation (%)	200	160
Breakdown Voltage (kV) mm ²	8	5.5



HT2 Ordering Information

Type	Width (W)	Length (m)	Thickness	Colour	Article-No.
HT2BK	18	20	0.18	Black (BK) ■	911-01103
HT2BL	18	20	0.18	Blue (BL) ■	911-01104
HT2WT	18	20	0.18	White (WT) □	911-01107
HT2GR	18	20	0.18	Green (GR) ■	911-01105
HT2RD	18	20	0.18	Red (RD) ■	911-01106
HT2YL	18	20	0.18	Yellow (YL) ■	911-01108
HT2GRYL	18	20	0.18	Green Yellow (GRYL) ■	911-01937

All dimensions in mm. Subject to technical changes

HT3 Ordering Information

Type	Width (W)	Length (m)	Thickness	Colour	Article-No.
HT3BK	19	10	0.13	Black (BK) ■	911-01109
HT3BL	19	10	0.13	Blue (BL) ■	911-01110
HT3WT	19	10	0.13	White (WT) □	911-01114
HT3GR	19	10	0.13	Green (GR) ■	911-01111
HT3RD	19	10	0.13	Red (RD) ■	911-01113
HT3YL	19	10	0.13	Yellow (YL) ■	911-01115

All dimensions in mm. Subject to technical changes

Recommended Industries for HT3:

