

Heat shrink pre-packs 2:1

Flame retardant* (black and colour)

- Shrink ratio 2:1
- Operating temperature F-55°C to +125°C
- Longitudinal change after shrinkage -5% max.
- Minimum shrink temperature +120°C
- Electrical connections, terminals, components and wiring systems
- Suitable for continuous insulation sleeve.





































SHSTDP (1m Pack).

RoHS ✓

Ordering Information

Type	Supplied IØ(D)	Recovery IØ(d)	Wall (WT) nom.	Material (p4)	Colour	Length (m)	Article-No.
CP24PBK	2.4	1.2	0.5	POX	Black (BK) ■	1	911-01258
CP24PBL	2.4	1.2	0.5	POX	Blue (BL) ■	1	911-01259
CP24PCL	2.4	1.2	0.5	POX	Clear (CL)* □	1	911-01260
CP24PRD	2.4	1.2	0.5	POX	Red (RD) ■	1	911-01261
CP24PWT	2.4	1.2	0.5	POX	White (WT) □	1	911-01262
CP24PYL	2.4	1.2	0.5	POX	Yellow (YL) ■	1	911-01263
CP32PBK	3.2	1.6	0.5	POX	Black (BK) ■	1	911-01264
CP32PBL	3.2	1.6	0.5	POX	Blue (BL) ■	1	911-01265
CP32PCL	3.2	1.6	0.5	POX	Clear (CL)* □	1	911-01266
CP32PGYS	3.2	1.6	0.5	POX	Green Yellow Stripe (GRYL) ■	1	911-01267
CP32PRD	3.2	1.6	0.5	POX	Red (RD) ■	1	911-01268
CP32PWT	3.2	1.6	0.5	POX	White (WT) □	1	911-01269
CP32PYL	3.2	1.6	0.5	POX	Yellow (YL) ■	1	911-01270
CP48PBK	4.8	2.4	0.5	POX	Black (BK) ■	1	911-01271
CP48PBL	4.8	2.4	0.5	POX	Blue (BL) ■	1	911-01272
CP48PCL	4.8	2.4	0.5	POX	Clear (CL)* □	1	911-01273
CP48PGYS	4.8	2.4	0.5	POX	Green Yellow Stripe (GRYL) ■	1	911-01274
CP48PRD	4.8	2.4	0.5	POX	Red (RD) ■	1	911-01275
CP48PWT	4.8	2.4	0.5	POX	White (WT) □	1	911-01276
CP48PYL	4.8	2.4	0.5	POX	Yellow (YL) ■	1	911-01277
CP64PBK	6.4	3.2	0.6	POX	Black (BK) ■	1	911-01278








Heat shrink pre-pack 2:1

Type	Supplied IØ(D)	Recovery IØ(d)	Wall (WT) nom.	Material (p4)	Colour	Length (m)	Article-No.
CP64PBL	6.4	3.2	0.6	POX	Blue (BL) 	1	911-01279
CP64PCL	6.4	3.2	0.6	POX	Clear (CL)* 	1	911-01280
CP64PGYS	6.4	3.2	0.6	POX	Green Yellow Stripe (GRYL) 	1	911-01281
CP64PRD	6.4	3.2	0.6	POX	Red (RD) 	1	911-01282
CP64PWT	6.4	3.2	0.6	POX	White (WT) 	1	911-01283
CP64PYL	6.4	3.2	0.6	POX	Yellow (YL) 	1	911-01284
CP95PBK	9.5	4.8	0.6	POX	Black (BK) 	1	911-01285
CP95PBL	9.5	4.8	0.6	POX	Blue (BL) 	1	911-01286
CP95PCL	9.5	4.8	0.6	POX	Clear (CL)* 	1	911-01287
CP95PGYS	9.5	4.8	0.6	POX	Green Yellow Stripe (GRYL) 	1	911-01288
CP95PRD	9.5	4.8	0.6	POX	Red (RD) 	1	911-01289
CP95PWT	9.5	4.8	0.6	POX	White (WT) 	1	911-01290
CP95PYL	9.5	4.8	0.6	POX	Yellow (YL) 	1	911-01291
CP127PBK	12.7	6.4	0.6	POX	Black (BK) 	1	911-01292
CP127PBL	12.7	6.4	0.6	POX	Blue (BL) 	1	911-01293
CP127PCL	12.7	6.4	0.6	POX	Clear (CL)* 	1	911-01294
CP127PGYS	12.7	6.4	0.6	POX	Green Yellow Stripe (GRYL) 	1	911-01295
CP127PRD	12.7	6.4	0.6	POX	Red (RD) 	1	911-01296
CP127PWT	12.7	6.4	0.6	POX	White (WT) 	1	911-01297
CP127PYL	12.7	6.4	0.6	POX	Yellow (YL) 	1	911-01298
CP190PBK	19	9.5	0.8	POX	Black (BK) 	1	911-01299
CP190PBL	19	9.5	0.8	POX	Blue (BL) 	1	911-01300
CP190PCL	19	9.5	0.8	POX	Clear (CL)* 	1	911-01301
CP190PGYS	19	9.5	0.8	POX	Green Yellow Stripe (GRYL) 	1	911-01302
CP190PRD	19	9.5	0.8	POX	Red (RD) 	1	911-01303
CP190PWT	19	9.5	0.8	POX	White (WT) 	1	911-01304
CP190PYL	19	9.5	0.8	POX	Yellow (YL) 	1	911-01305
CP254PBK	25.4	12.7	0.9	POX	Black (BK) 	1	911-01306
CP254PBL	25.4	12.7	0.9	POX	Blue (BL) 	1	911-01307
CP254PCL	25.4	12.7	0.9	POX	Clear (CL)* 	1	911-01308
CP254PGYS	25.4	12.7	0.9	POX	Green Yellow Stripe (GRYL) 	1	911-01309
CP254PRD	25.4	12.7	0.9	POX	Red (RD) 	1	911-01310
CP254PWT	25.4	12.7	0.9	POX	White (WT) 	1	911-01311
CP254PYL	25.4	12.7	0.9	POX	Yellow (YL) 	1	911-01312

All dimensions in mm. Subject to technical changes.

*Clear is not self extinguishing

Pre-Pack multiple sizes and colours: Ordering Information

Type	Supplied IØ(D)	Material (p4)	Colour	Length (m)	Qty	Article-No.
CPPKITBK	2.4 – 4.8	POX	Black (BK) 	1	x10 of each	911-01313
	6.4 – 25.4				x5 of each	
CPPKITCOL	2.4 – 12.7	POX	BL,  YL,  RD,  CL*,  WT,  GRYL 	1	x5 of each	911-01314
	19.0-25.4				x2 of each	

Recommended Tools

Type	HG2120E	HL1920E	HL1620S
Page	114	114	114